

Bitterfeld-Wolfen, 2017-06-09
Reference: TMS_0734

General release of 3° mounting without functional grounding

Dear Sir or Madam,

Hanwha Q CELLS permits the mounting of the Q CELLS modules listed below with a tilt of ≥ 3 degrees for installations located outside of the tropics (between 23.5°N and 23.5°S), without functional grounding at the negative generator connection.

For these locations and products the requirement for functional grounding as stated by the installation manual for 3-5° tilts can be disregarded.

Applicable modules:

Q.PRO-G4 / Q.PRO BFR-G4 / Q.PRO BLK-G4 / Q.PRO BFR-G4.1

Q.PLUS BFR-G4.1 / Q.PLUS BFR-G4.1 / Q.PLUS-G4.2 / Q.PLUS BFR-G4.2 / Q.PLUS-G4.3

Q.PEAK-G4.1 / Q.PEAK BLK-G4.1

Q.PRO L-G4.1 / Q.PRO L-G4.2 / Q.PLUS L-G4.1 / Q.PLUS L-G4.2

Kind regards,



Mr. D. Felsch-Kruse,
Director QM / FG & CM
Hanwha Q CELLS



Mr. M. Schurade,
Director Technical Marketing Support
Hanwha Q CELLS